


MODEL TXB-RHUL UL762 LISTED RESTAURANT BELT DRIVE CENTRIFUGAL UPBLAST ROOF EXHAUSTER

P: 800.961.7370 www.solerpalau-usa.com



AVG. **DIMENSIONS (IN.)** SIZE SHIP WT. В Α С Е D (LBS) 30 42 1/2 56 3/4 41 45 2 1/2 365 42 1/2 66 48 2 1/2 36 44 365 42 72 1/2 48 52 55 2 1/2 385 48 55 78 3/4 52 56 2 1/2 490

A - Inside dimension of square curb cap. B - Outside diameter of unit.

D - Height of unit above top of curb.

G - Outside dimension of factory built prefab curb.

C - Height of exhaust opening above curb cap.

OPTIONAL (Must be specified)

cULus 762 (Grease)

cULus 705

FAN FEATURES

- Exhaust air up to 35,000 CFM in high static pressure applications up to 3-1/4" w.g.
- Attractive spun aluminum exterior •
- Belt drives permit easy performance adjustments when needed
- Non-overloading backward inclined wheel for efficiency at higher static pressures
- Roof or sidewall mounting options •
- UL 705 listed •
- . UL 762 listed for Grease Removal

		METAL GAUGES										
	SIZE	WIND	MOTOR		BASE							
		BAND	COVER	SHROUD	STD/UL	RHUL						
	30	.050	.050	.100	.090	16GA						
	36	.050	.050	.090	.090	16GA						
	42	.050	.050	.090	.100	N/A						
	48	.050	.050	.090	.100	N/A						

FAN SPECIFICATIONS								MOTOR SPECIFICATIONS					
Line	Qty.	Model No.	Tag	CFM	SP	Fan RPM	BHP	Sones	HP	Volts	Phase	Hertz	Encl
1													
2													
3													
4													
5													

ACCESSORY ITEMS	1	2	3	4	5	ACCESSORY ITEMS	1	2	3	4	5	
Project: Submitted:												
Project: Submitted: Customer: Approved:												

Customer: Location:

